

HUE RGB+ SERIES



INTERIOR



Date: _____ Project: _____ Type: _____

Ordering Guide:

Series	CCT	Output/Foot	Length
HUE	RGB27 (RGB+2700K) RGB30 (RGB+3000K) RGB41 (RGB+4100K) RGBAM (RGB+Amber) RGB272 (RGB+[2]2700K) RGB302 (RGB+[2]3000K) RGB412 (RGB+[2]4100K) RGBAM2 (RGB+[2]Amber)	HO (5.86watts) SHO (7.02watts) HO2 (7.32watts)	100 (full reel - 100 feet) CC @XX (custom cut, specify footage)



Features:

- 120° beam angle
- 24 Volt
- CRI 90+
- Field cuttable
- 50,000 hour life
- 5 year warranty
- IP20

Note: Drawings not to scale.

Model Number	HUE-RGBXX-HO	HUE-RGBXX-SHO	HUE-RGBXX2-HO2
Lumens/foot	Red 40	45	40
	Green 85	100	85
	Blue 35	40	35
Plus	2700K 125	150	250
	3000K 130	155	260
	4100K 135	160	270
	Amber 40	45	80
Watts/foot	5.86	7.02	7.32
Cut section length	3.92"	3.35"	3.92"
Diode spacing (pitch) O.C.	0.66"	0.56"	0.66"
Diodes per foot	19	22	19
Maximum run length	16'	13'6"	13'

98.4' bulk reels supplied with 24" soldered lead & (15) ribbon to power supply connectors
 Custom cut lengths supplied with 24" soldered lead standard - longer lead can be specified

All Omnilight products are tested and warranted for use exclusively with Omnilight power supplies

OL1