

# True Series

COB : static white : IP20







Date: \_\_\_\_\_ Project: \_\_\_\_\_ Type: \_\_\_\_\_

Model Number	TRU-XX-AO	TRU-XX-SO	TRU-XX-HO	TRU-XX-SHO
Lumens/foot	2200K	230	322	412
	2400K	128	259	373
	2700K	137	268	382
	3000K	146	283	397
	3500K	156	293	406
	4100K	162	298	412
Watts/foot	1.53	3.05	4.27	5.49
Cut section length	2.19"	2.19"	1.79"	1.51"
Diode spacing (pitch) O.C.	NA	NA	NA	NA
Diodes per foot	NA	NA	NA	NA
Maximum run length	35'	31'	22'	17'



100' bulk reels supplied with 24" soldered lead & (15) ribbon to power supply connectors  
 Custom cut lengths supplied with 24" soldered lead standard - longer lead can be specified



\*SHO ribbon must be mounted in channel

## Ordering Guide:

Series	CCT	Output/Foot	Length
<b>TRU</b>			
TRU (IP20)	<b>22</b> (2200K) <b>24</b> (2400K) <b>27</b> (2700K) <b>30</b> (3000K) <b>35</b> (3500K) <b>41</b> (4100K)	<b>AO</b> (1.53 watts) <b>SO</b> (3.05 watts) <b>HO</b> (4.27 watts) <b>SHO</b> (5.49 watts)	<b>100</b> (full reel - 100 feet) <b>CC @XX</b> (custom cut, specify footage)



All Omnilight products are tested and warranted for use exclusively with Omnilight power supplies